AFWL-TR-78-158, Pt. 3

AFWL-TR-78-158 P1. 3

4071 522

MA071523

SIMULATION DEVELOPMENT FOR TARGET ASSESSMENT

Part 3 of 3

J. A. Earickson

Eric H. Wang Civil Engineering Research Facility University of New Mexico Albuquerque, NM 87131

March 1979

Final Report

Approved for public release; distribution unlimited.

COPY FILE COPY

AIR FORCE WEAPONS LABORATORY
Air Force Systems Command
Kirtland Air Force Base, NM 87117



This final report was prepared by the Eric H. Wang Civil Engineering Research Facility, under Contract F29601-76-C-0015, Job Order 88091323 with the Air Force Weapons Laboratory, Kirtland Air Force Base, New Mexico. Lt Williams (DED) was the Laboratory Project Officer-in-Charge.

When US Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This report has been authored by a contractor of the United States Government. Accordingly, the United States Government retains a nonexclusive, royalty-free license to publish or reproduce the material contained herein, or allow others to do so, for the United States Government purposes.

This report has been reviewed by the Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

Lt. USAF

Project Officer

FOR THE COMMANDER

RUDOLPH V. MATALUCCI

Lt Colonel, USAF

Chief, Simulation Branch

STEWART W. JOHNSON Lt Colonel, USAF

Chief, Civil Engineering Research

Division

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)


REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM	
T. REPORT NUMBER AFWL-TR-73-158, Pt. 3	3. RECIPIENT'S CATALOG NUMBER	
4. YITLE (and Subitto)	S. TYPE OF REPORT & PERIOD COVERED	
SIMULATION DEVELOPMENT FOR TARGET ASSESSMENT	Final Report	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(a)	8. SONTRACT OR GRANT NUMBER(s)	
J. A. Earickson	F29601-76-C-0015 -	
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT RUMBERS	
Eric H. Wang Civil Engineering Research Facility	6260'rF	
University of New Mexico Albuquerque, NM 87117	88091323	
11. CONTROLLING OFFICE MAME AND ADDRESS	IZ. REPORT DATE	
Air Force Weapons Laboratory (DED)	March 1979	
Kirtland Air Force Base, NM 87117	13. NUMBER OF PAGES	
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	18. SECURITY CLASS, (of this report)	
	UNCLASSIFIED	
	18a. DECLASSIFICATION/DOWNGRADING	
16. DISTRIBUTION STATEMENT (of this Paport)		
17. DISTRIBUTION STATEMENT (of the obstract entered in Block 20, if different from Report)		
In. SUPPLEMENTARY HOTES		
This report consists of 3 parts. Part 1 contains the front matter and pages 1 to 178. Part 2 contains pages 179 to 364- Part 3 contains pages 365 to 530.		
19. KEY WORDS (Continue on reverse side if necessary and identity by block manuer) Simulator HEST (High Explosive Simulation Sechnique) Target Assessment Air Sheck		
DThis effort produced design information and experiment data for improving high explosive simulation of nuclear airblasts. Specifically, a peak pressure versus charge density relationship for Iremits in 100 percent foam cavities was obtained for pressure up to 68 MPa. The results of this effort were transmitted to USAE Waterways Experiment Station. WES is conducting tests on generic silos as part of a DNA targeting research and test program.		


DD 1 JAN 79 1473 KEDITION OF 1 NOV 65 IS OSSOLETE


UNCLASSIFIED


APPENDIX B DOUBLE-EXPONENTIAL PEAK PRESSURE OVERLAY PLOTS AND CALCULATED RESIDUALS VERSUS X-COORDINATED PLOTS


Accession For		
NTIS DDC To Unanno	GRA&I	X
	Putdon/	
Dist	obility C Avail and/ special	

























STATE OF THE STATE




























The second of the second


















PRESSURE (PSI)








A STATE OF THE STA











-20000-

-100001-


PRESSURE (PSI)

100001


Ö


-40000


-30000-





Art is skill































ze Ves.




















PRESSURE (PSI)

000


5000

IN HEST-2


10000


900

2000





A







The Contract of the Contract o








Maria Company


























SCO

ርን

10000


The same of the same of the same


8000


9


5

PRESSURE (PSI)












(i) t_i <


PRESSURE (PSI)








Man Literated to Security













THE RESERVE AND ADDRESS OF THE PARTY.

and the second



To made the Hilliam





The second second

10 -

47

THE SHARM NAME AND








เมษา โรสเษรากสเท


. . . .


2














意味を


The state of the s







これでは、一般のであるからには、これはこれをなって、これがいいまっといれから







The state of the second









{








Water Branch College


42



















1. The FAR Court 1 . . .
















Control of the Control of the Land Control






























In which











A company of the second second



















Jan Carrie





\$


PRESSURE (PSI)


12000 -























































VSN-TAPE22 FILE-4 E.U. =0.300,4108.000 DIGITS=0.000,675.000 8 50 AM, 2 MAY 78. -10C.00 KHZ TSKIP=12.640 S.R. = 10°






















PRESSURE (PSI)


















Ċ











MA





















505/505


APPENDIX C PLOTTED PHOTOPOLE DATA































and the second second











APPENDIX D

TEST INSTRUMENTATION DETAILS

		Page
TA HEST 1:	BLAST PRESSURE MEASUREMENTS	522
	TIME-OF-ARRIVAL MEASUREMENTS	523
TA HEST 2:	BLAST PRESSURE MEASUREMENTS	524
	TIME-OF-ARRIVAL MEASUREMENTS	525
TA HEST 3:	BLAST PRESSURE MEASUREMENTS	526
	TIME-OF-ARRIVAL HEASUREMENTS	527

Test: TA HEST 1 - Blast Pressure Measurements Date: February 24, 1978

							Locations			Posttest
Munder Number	Kumber	Type	Shield	As Planned, in	red.	Ë	As	As Built, in		Change (AZ),
				×	>	2	×	Å	7	e,
1	2-7	Kulite 30K	10	+2	+12	0	+5	+12-1/4	0	-12.06
2	Ţ	Fullte 20K	8	-36	09+	0	-36	+60-1/4	0	-11.04
m	9-4	Kultte 20K	8	-36	-36	0	-35-3/4	-36-3/8	+3/16	-11.04
•	5-22	Kulite 20K	82	-36	-36	0	+36-1/2	-36-3/8	+1/8	-11.46
ĸ	351	Bar SK	Mone	(N) +	φ	0	+2-1/8	-6-1/8	+1/16	-11.88
vo	353	Bar 6K	None	+1-3/8	-18	0	+15/16	-18	+1/16	-11.64
F *	357	Bar 6K	None	+3/4	-30	0	+3/4	-30-1/4	+3/16	-11.04
6 7	362	Bar 6k	None	0	-42	()	-1/4	-42-1/2	+3/16	-10.62
									Averag	Average = -11.35

TA HEST 1 - Time-of-Arrival (TOA) Measurements

Mesurement	Gage,	Lo	cations,	in	TOAD,
Number	Type	X	Y	2	ms.
1		+72	+24	+3-3/4	
2		+36	0	+3-3/4	
3		0	+24	+3-3/4	
4		-36	0	+3-3/4	
5		-72	+24	+3-3/4	
6		+72	-72	+3-3/4	
7		+36	-48	+3-3/4	
8		0	-72	+3-3/4	
9		-36	-48	+3-3/4	}
10		-72	-72	+3-3/4	
11		0	+12	+3-3/4	
12		0	0	+3-3/4	
13		0	-12	+3-3/4	
14		+72	+72	+5-3/8	
15		+36	+48	+5-3/8	
16		0	+72	+5-3/8	Ì
17		-36	+48	+5-3/8	
18		-72	+72	+5-3/8	
7.9		+72	-24	+5-3/8	}
26	Ì	+36	-48	+5-3/8	
2.	Ì	0	-24	+5-3/8	
22		-36	-40	+5-3/8	
23		-72	-24	+5-3/8	

All gages were crystal type.

Data unavailable due to pin pox failure.

Tess: TA HEST 2 - Blast Pressure Measurements Date: March 24, 1978

							Locations			Posttest
Heasurgeant Measur	Sugar Arren	Type	Shield	As P1	As Planned, in	÷	As	As Built, in		Change (AZ),
				×	٨	1	×	Y	1	=
_	-	Kulite 20K	81	+57	0	0	+57	0	+1/8	-8.52
ru.	4-5	Kulite 20K	15	+36	+12	0	+35-1/2	+12	÷3/18	-8.16
ຠ	§- 22	Ku!1te 20K	80	+21	-48	0	+21	8	+3/16	-6.54
+	2-7	Kalite 30K	92	0	0	0	0	0	0	-7.38
ιñ	5~23	Kulite 20K	<u></u>	-21	+48	0	-21-3/8	+48	ဝ	-6.90
ø	5-37	Kulite 20K	18	-36	-12	0	-36	-11-3/4	+1/16	-6.72
.~	355	sar 6K	None	+12	0	C	+12-5/16	0	+1/16	-7.38
			i						Averā	Average = -7.37

TA HEST 2 - Time-of-Arrival (TOA) Measurements

Measurement	Gage_	Ĺ	ocation,	in	TOA,
Number	Gage _a Type ^a	X	Y	Z	ms
. 1		+72	+24	+3-3/4	0.523
2		+36	0	+3-3/4	0.687
3		0	+24	+3-3/4	0.842
4		-36	0	+3-3/4	1.006
5		-72	+24	+3-3/4	1.162
ε		+72	-72	+3-3/4	0.522
7		+36	-48	+3-3/4	0.683
8		0	-72	+3-3/4	0.849
9		-36	-48	+3-3/4	1.010
10		-72	-72	+3-3/4	1.165
11		0	+12	+3-3/4	0.934
12		0	0	+3-3/4	1.153
13		0	-12	+3-3/4	Failed
14		+72	+72	+5-3/8	0.532
15		+36	+48	+5-3/8	0.692
16		0	+72	÷5-3/8	0.946
17	l.	-36	+48	+5-3/8	1.020
18		-72	+72	+5-3/8	Failed
19		+72	-24	+5-3/8	0.531
20		+36	-48	+5-3/8	0.683
21		C	-24	+5-3/8	0.857
22		-36	-48	+5-3/8	1.019
23	<u></u>	-72	24	+5-3/8	1.160

^aAll gages were crystal type.

· Water to the william

Test: TA MEST 3 - Blast Pressure Measurements Date: April 27, 1978

The Control of the Control

						12	Locations			Posttest
Measurement	Gège	Gage	Debris	As Planned	ned.	46	As 3c	3411t,	ft	Change (AZ).
Number	Number	Type	Shield	×	>	7	×	>	2	-tn
	,	30%	10	+7.0	Ŧ	0	6.968	1+	0.0	-18.12
- (7-7	۲ کر در	2 5	+7.0	7	0	6.974	-	+0.03	-17.40
8	b- 7	Y 20 0	2 5	+14.0	4	0	14.000	7	9.0	-15.36
(°)	2-5	SOS .	2 ;		-		14.000	7	+0.02	-15.24
♥	5-9	30K	<u> </u>) +	7	> 6		7	\$0 U+	-13.92
S	2-11	30K	0	+21.0	-	-	20.12	<u> </u>	3 5	-12 72
9	2-12	30K	2	+21.0	-	0	50.989	-	+0.06	27.71
. ~	4-3	20K	∞	+28.0	∓	0	28.000	-	5	-16.46
~ 00	4-4	20K	82	+28.0	7	0	28.000	7	-0.0	88 . :
	A .	20K	8	+35.0	Ŧ	0	34.989	T	-0.67	-12.88
F ;	•	30,	<u> </u>	+35.0	<u>-</u> -	0	34.979	7	-0.05	-10.92
e 	•	5 8	2	142 0	-	0	42.000	~	-0.69	-12.34
=		X02	<u> </u>			•	72 000		-0.03	-11.52
12	-1	20K	6	+42.0	-	5	3	-	2	. 13.20
13	4-14	20K	e	0.67+	-	ت	3.5	<u>-</u>	3 6	
71	4-27	20K	8	+49.0	7	0	43.968	-	5	25.35
<u> </u>	5-21	20K	8 2	+56.0	=	0	\$6.020	=	-0.10 -	52.21
<u> </u>	200	20K	<u>e</u>	+56.0	-	•	26 .000	=	-6.1	-15.00
<u> </u>	77.0	2 2		1 +63.0	=	•	63.000	7	\$ ••	3 .
<u> </u>	2 2	5 6	<u> </u>	.63.0	<u>-</u>	0	63.000	7	-0.07	-11.52
89 (07-6	1	<u> </u>	+24.5	-	<u> </u>	24.500		-0.0	-12.24
5	ci-2	5 6	2 9	746 6		_	45.468	-	9.0	.11.8
20	75-3/	Š	2			4			Averes	ege13.07

Anil gages were Kulite type.

TA HEST 3 - Time-of-Arrival (TOA) Measurements

Hassurement	Gage	L	ocations, f	t I	TOA.
Reber	Type	1	Y	7	eng.
1		0.0	+4.0	0.312	0.400
2		0.0	0.0	0.312	0.440
2	j	0.0	-4.0	0.312	0.465
4	Í	9.0	0.0	0.312	0.825
5		18.0	44.0	0.312	1.309
6	ł	18.0	-4.0	0.312	1.266
7	1	27.9	+4.0	0.312	Failed
8		27.9	C.0	0.312	1.692
	1	27.9	-4.0	0.312	8.712
10 11		35.9	+2.0	0.312 0.312	2.070 2.266
	1	40.4	+4.0	0.312	2.29
12 13)	40.4	0.0	0.312	2.297
14]	40.4 44.4	-4.0 +2.0	0.312	2. 488
15		47.9	0.0	0.312	2.661
16	1	50.9	+2.0	0.312	2.821
17	İ	53.8	+4.0	0.312	2.975
18	1	53.8	0.0	0.312	2.973
19	1	53.8	-4.0	0.312	2.993
20		56.5	+2.0	0.312	3.124
21		59.2	0.0	0.312	3.273
22	1	61.7	+2.0	0.312	3.416
23		64.6	+4.0	0.312	3.552
24		64.0	0.0	0.312	3.569
25	1	64.0	-4.0	0.312	3.551
26		66.3	+2.0	0.312	3.683
27		68.5	0.0	0.312	3.819
28		0.0	e4.0	0.447	Failed
29	1	0.0	0.0	0.447	0.442
30	1	0.0	-4.0	0.447	0.,489
31	[9.0	+4.0	0.447	0.896
32		9.0	-4.0	0.447	0.885
33	l	18.0	0.0	0.447	1.258
34	1	27.9	+4.0	0.447	1.715
35	1	27.9	0.0	0.447	1.701
36		27.9	-4.0	0.447	1.731
37	1	10.4	0.0	0.447	2.290
38	1	47.9	+4.0	0.447	2.674
39	1	47.9	0.0	0.447	2.666
40	}	47.9	-4.0	0.447	2.687
41		53.8	0.0	0.447	2.961
42		59.2	+4.0	0.447	3.265
43	1	59.2	0.0	0.447	3.280
64	1	59.2	-4.0	0.447	3.296
45	1	64.0	0.0	0.447	3.559
46	· Į	68.5	+4.0	0.447	3.826
47		68.5	0.G	0.447	3.825
48		68.5	-4.0	0.447	3.825

^aAll gages were crystal type.

APPENDIX E HEST LOCKUP COOC DESCRIPTION

The lockup impulse code is used to calculate HFST pressure and impulse histories for a given initial pressure, earley, and overturnes dimensions soft properties, as well as the ratio of specific hasts (r) of the detruntion products. The code is small enough to run on the HP \$220h programmeble raiculator, and a BASIT version for the lektronix 4051 is available. No provision i, made for handling lapered soils; the overturnes and test had materials are assumed uniform and tomogeneous. The calculations are open-dimensional, and the three-dimensional properties of a HEST calculation are approximated. The detonation product/air win in the cavity is assumed to have a uniform product/air min by assumed to be a "gamma law" gas with gamma had constant. The lockum code is typically used to design a HEST so that its pressure bijarary matches a given nuclear moveform. This is done by varying cavity and overherden dimensions until the calculated HEST waveform most closely notices the design nuclear navegarance.

The code is also used in the analysis of data obtained from a NEST test. In this case, one inputs the appropriate soil model, as-built dimensions etc., into the code and varies the initial pressure until the calculated MEST imprise-time trace most closely matches the given data trace. This initial pressure is called the Simulation Peak Pressure. This method of determining peak pressures is an alternative to using the peak pressure routine^a. In fitting a data trace with the lockup code the user determines the quality of the fit by inspection. Since these MESTs were designed with the lockup code, fitting data traces with the code yields information about the quality of the simulation. The lockup code should be used in the analysis of HEST test data whenever the results of that analysis are to be used as inputs in future HEST designs.

^{*}thampler. Howard W., and Earickson, Jeff A., High-Pressure and Foam HEST Analyses, CERF AST-10, Civil Engineering Research Facility, University of New Mexico, Albuquerque, New Mexico, publication pending.